



nusantara
T E A K

Roman Arch Hammock Stand Assembly Instructions

1. EYE BOLTS (2 Eye Bolts, 2 Washers, 2 Nuts)

- Fix the eye bolts to each wooden segment that has a center hole where there is a logo cap.
- Use a washer on the front and rear end of the bolt. The rear washer fits into the countersunk hole.
- These will be the center segments



2. MAKING THE ARCH (4 Long Bolts, 8 Washers, 8 Nuts)

- Align the 2 base segments side by side, leaving enough space for the center segments in between
- Place a center segment in between the base segments and align the side holes
- Ensure that the countersunk holes are on the outside to fit the washer and nuts
- Place a nut and washer on one end of the 4 long bolts, and pass the long bolt through the side of all three segments
- Place a washer and nut on the other end of the bolt, and repeat this step with the remaining holes.
- Once all 4 bolts and nuts are secured, tighten all nuts on the bolts with a 13mm socket.



3. FOOT SEGMENTS

(4 Fixed Head Bolts, 8 Washers, 4 Nuts)

- Place one foot segment underneath the base aligning the countersunk holes on the base with the holes on the legs
- Ensure that the open recess on the legs is facing the center of the arch
- Drop the fixed head bolts into the countersunk hole on the outer base segments with a washer, and pass the bolt through the feet segments.
- Fasten a nut and washer on the bolt underneath, which will now be protruding from the countersunk hole on the bottom of the leg segment
- Repeat this step for the other foot segment, and secure the nuts to the bolts



4. CONFIRM ALL NUTS ARE SECURELY FASTENED WITH A 13mm SOCKET BEFORE USE!

5. HANG THE DREAMWEAVER HAMMOCK

(2 Chains, 4 Quick- Clips)

- Attach the quick clips to each chain, and one clip to the eye bolts on the center segment
- Fasten the other quick clip to one end of the hammock rings, and repeat on the opposite end.
- Adjust the tension by adjusting the length of the chain.

